

## LIFTING TABLE 350KG



Recommended for lifting, lowering, and transporting to the desired working height. Lifting by means of a hydraulic pedal and lowering by means of a lever. With two fixed wheels and two directional wheels with brake. Easy to operate, the brake keeps the unit stationary in loading and unloading, while the lowering valve provides precise height lowering, reducing effort and fatigue, used for lifting, transporting, positioning, assembling, stacking, and unstacking.

### TECHNICAL SPECIFICATIONS

Technical details		
Capacity kg		350
Max. lifting height mm		1300
Min. table height mm		350
Elevation height mm		950
Table dimensions mm		910x500x50
Total height mm		970
Overall length mm		980
Pedal cycles for max. height		≤ 60
Wheel diameter mm		127
Weight kg		105
Volume of oil cylinder (working) ml		165
Oil capacity ml		250

SAP	DESCRIPTION	EAN
CHU010100100350	Lifting table 350Kg	5604630167925

**Note:** The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products according to our standards.