

# CHEMICLEAN INDUSTRIAL CLEANING CREAM

## CHEMICLEAN

### INDUSTRIAL CLEANING CREAM



#### optional accessory

#### WALL SUPPORT



## PRODUCT DESCRIPTION

**CHEMICLEAN Industrial Cleansing Cream** Hand washing cream concentrated with mineral microspheres and enriched with sericin, to remove dry and greasy dirt, leaving hands soft. With excellent cleaning and softening properties, the latter being dictated by the presence of sericin, a natural protein derived from silk.

## CHARACTERISTICS

- ❖ High cleaning power with high degreasing power
- ❖ Excellent cleaning properties.
- ❖ Contains mineral microspheres that give greater strength to its cleaning action
- ❖ Pleasant creamy consistency with sandalwood aroma
- ❖ Enriched with sericin, the silk protein, with a moisturizing effect that keeps the skin smooth.
- ❖ With emollient and moisturizing substances.
- ❖ Free of silicone and solvents. Biodegradable product
- ❖ Hygienic, as it is dosed through a dispenser
- ❖ Advised for frequent use.
- ❖ Mineral microspheres (Plastic-free)
- ❖ Super concentrated
- ❖ High skin compatibility. dermatologically tested
- ❖ Eliminates bad smells, leaving hands pleasantly scented
- ❖ Does not clog pipes
- ❖ High profitability, provides approximately 1670 doses

## TECHNICAL SPECIFICATIONS

Properties	
Ingredients	Aqua (water), calcium carbonate, sodium tallowate, sodium laureth sulfate, silica, sodium dodecylbenzenesulfonate, cocamide-DEA, ocamidopropyl betaine, laureth-4, sodium lauryl sulfate, cellulose, sericine, glycerin, carbomer, propylen glycol, parfum (fragrance), methylchlorisothiazolinone, methylisothiazolinone, CI 16255
Physical Appearance	Cream
Odor	Sandalwood perfume
Color	Red
Solubility in water	Complete
Specific Weight at 55°C	1000+/- 30g/l
pH	8,5 +/- 0.3

Results tested in the laboratory.

## APPLICATIONS

Indicated to remove any type of difficult dirt from the hands, including lubricating oils, grease, varnish, paint, enamel, putties, glues, graphite, grease, uncured sealants and adhesives, resins, rust, coal, etc.

Recommended for professional use (mechanics, painters, plumbers, among others).

## METHOD OF APPLICATION

### APPLICATION

- Put a small amount of product in your hands
- Rub well with dry hands until the dirt is completely removed.
- Rinse with plenty of water.

## TESTS

### Patch Test

The product remains in contact with the skin of a set number of volunteers, using patches, keeping it that way for 48 hours to check for the possible appearance of allergic reactions.

### Provocation Test

Procedure used to verify the microbiological stability of the product over time. The test consists of the inoculation of bacteria in the sample; Their number has to decrease in a quick time by the action of the preservative

ISO 9001 and ISO 14001 certified factory

## SAFETY INFORMATION

Eye contact: rinse with plenty of water and consult a doctor if irritation persists.

Ingestion: Rinse mouth with water without swallowing, seek medical advice immediately and show the label or packaging.

## STORAGE CONDITIONS AND SHELF LIFE

Store in a cool, dry, well-ventilated environment between +10°C and +35°C, away from heat sources and direct sunlight.

The product preserved according to the instructions can be stored for 36 months. Once opened, use within a maximum period of 12 months is recommended.


## REGULATION

The product is subject to the obligations of EC Regulation 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products.

Product not subject to EC Regulation 1272/2008 (CLP) of the European Parliament and of the Council of 16 December 2008 on the classification, labeling and packaging of substances and mixtures, which amends and repeals Directives 67/548/EEC and 1999/45/ EC and amends Regulation (EC) No 1907/2006 (REACH) as indicated in art. 1 section 5 letter C.

REGISTRATION at CPNP No. 4169148

## PACKAGING

SAP	SPECIFICATION	VOLUME L		EAN
CH24000006	CHEMICLEAN INDUSTRIAL CLEANING CREAM	5	4	5604630159517
CH24000008	CHEMICLEAN WALL SUPPORT		1	5604630159531

**Note:** This technical data sheet cancels and replaces others previously issued for the same product. The technical information given, verbally or in writing, is based on our current knowledge, given in good faith and supported by various laboratory tests. Taking into account the diversity of factors that may affect the product during its use, as well as the various application techniques, the user is responsible for confirming and carrying out his own tests and experiments, whether the product is suitable for the process and type. of use in question. For these reasons, any application of the product is carried out under the sole responsibility of the user, and CHEMITOOL-LUSAVOUGA S.A. cannot. be liable for any losses or damages, directly or indirectly resulting from the application. All features, specifications and product images are subject to change without notice.