

## ROTO-ORBITAL PNEUMATIC SANDER

### 150 MM roto-orbital sander.

Durable performance without operator fatigue.  
Designed to increase operator productivity.

### Smooth operation.

Ideal for sanding and surface preparation on wood, metal, fiberglass and composite materials, and many other substrates.

### Fields of application.

Grinding.  
Grinding (normal, fine, aggressive, masking, preparation).

### Included.

Dust bag.  
Suction hose.

### Features.

Aluminium alloy housing.  
Smooth operation, low noise, low vibration and no hand fatigue after long time use.  
Self-priming dust collection device to prevent inhalation and reduce environmental pollution.  
High quality bakelite rotor blade, durable and difficult to deform.



Pressure switch



Air inlet/outlet



Disc base



Suction hose



Speed adjustment knob

## TECHNICAL SPECIFICATIONS

SAP	CHT6010011215050
Disc diameter	150 mm
Maximum speed	12000 rpm
Air inlet	1/4 "
Air connection (hose)	3/8 "
Average air consumption	79,2 Lt/Min
Suggested compressor power	2 Hp
Eccentric	5 mm

**Note:** The technical information provided orally or in writing is based on our current knowledge and is to be considered as non-binding cooperation. The use of the product is beyond our control and we decline any liability for improper use of the product. The customer is responsible for confirming and evaluating (by testing) whether the product is suitable for the process and type of use in question. Our aim is exclusively to guarantee the quality of the products in accordance with our standards.