

IDENTIFICATION:	CH0231
EDITION:	MAY 2023
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231

1. Unique identification code of the product-type:

NEUTRAL ULTIMATE AY CHEMISIL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural use in joints in buildings for exterior and in accordance with the European standard EN 15651-1:2012 Type F EXT-INT**Sealant for glass application: EN 15651-2:2012 Type G Class 25 LM**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

CHEMITOOL®
LUSAVOUGA- Máquinas e Acessórios Industriais, S.A.
Avenida Europa, 375
3800-533 Cacia – Portugal

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified body No. 0074 - GINGER CEBTP, carried out the product type determination tests, based on the test type in system 3 and issued the test report.**Notified body No. 1234 - EFECTIS, carried out the class determination tests regarding the reaction to fire, in system 3 and issued the test report.**

IDENTIFICATION:	CH0231
EDITION:	MAY 2023
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231

8. Declared performance:

EN 15651-1: Type F EXT-INT

ESSENTIAL FEATURES	DECLARED PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATIONS
Reaction to fire (classification according to EN 13501-1:2007)	Class E	EN 15651-1 :2012
Release of hazardous chemicals to the environment and health	NPD	
Water and air tightness		
Volume loss (EN ISO 10563)	≤ 10 %	
Flow resistance (EN ISO 7390)	≤ 3 mm	
Tensile properties • in extension maintained after immersion in water (according to EN ISO 10590)	Approved	
Elastic recovery (according to EN ISO 7389)	≥70 até 100%	
Durability	Approved	

Conditioning: Method A

Substrate: Facade: Anodized Aluminum + M2 Concrete

EN 15651-2: Type G

ESSENTIAL FEATURES	DECLARED PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATIONS
Reaction to fire (classification according to EN 13501-1:2007)	Classe E	EN 15651-2 :2012
Release of hazardous chemicals to the environment and health	NPD	
Water and air tightness		
Volume loss (EN ISO 10563)	≤ 10 %	
Flow resistance (EN ISO 7390)	≤ 3 mm	
Adhesion-cohesion properties after exposure to heat, water and artificial light (as per EN ISO 11431)	Approved	
Elastic recovery (according to EN ISO 7389)	≥70 até 100%	
Durability	Approved	

Conditioning: Method A

Substrate: Glazing: Glass

IDENTIFICATION:	CH0231
EDITION:	MAY 2023
VERSION:	1

INGLÊS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231

9. Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nuno Miranda
Diretor da QualidadeRaquel Elias
Gestora de Produto

Aveiro (Portugal), 01.06.2023

IDENTIFICATION:	CH0231T
EDITION:	MAY 2023
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231T

1. Unique identification code of the product-type:

NEUTRAL ULTIMATE AYT CHEMISIL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural use in joints in buildings for exterior and in accordance with the European standard EN 15651-1:2012 Type F EXT-INT

Sealant for glass application: EN 15651-2:2012 Type G Class 25 LM

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

CHEMITOOL®
LUSAVOUGA- Máquinas e Acessórios Industriais, S.A.
Avenida Europa, 375
3800-533 Cacia – Portugal

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified body No. 0074 - GINGER CEBTP, carried out the product type determination tests, based on the test type in system 3 and issued the test report.

Notified body No. 1234 - EFECTIS, carried out the class determination tests regarding the reaction to fire, in system 3 and issued the test report.

IDENTIFICATION:	CH0231T
EDITION:	MAY 2023
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231T

8. Declared performance:

EN 15651-1: Type F EXT-INT

ESSENTIAL FEATURES	DECLARED PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATIONS
Reaction to fire (classification according to EN 13501-1:2007)	Class E	EN 15651-1 :2012
Release of hazardous chemicals to the environment and health	NPD	
Water and air tightness		
Volume loss (EN ISO 10563)	≤ 10 %	
Flow resistance (EN ISO 7390)	≤ 3 mm	
Tensile properties • in extension maintained after immersion in water (according to EN ISO 10590)	Approved	
Elastic recovery (according to EN ISO 7389)	≥70 até 100%	
Durability	Approved	

Conditioning: Method A

Substrate: Facade: Anodized Aluminum + M2 Concrete

EN 15651-2: Type G

ESSENTIAL FEATURES	DECLARED PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATIONS
Reaction to fire (classification according to EN 13501-1:2007)	Classe E	EN 15651-2 :2012
Release of hazardous chemicals to the environment and health	NPD	
Water and air tightness		
Volume loss (EN ISO 10563)	≤ 10 %	
Flow resistance (EN ISO 7390)	≤ 3 mm	
Adhesion-cohesion properties after exposure to heat, water and artificial light (as per EN ISO 11431)	Approved	
Elastic recovery (according to EN ISO 7389)	≥70 até 100%	
Durability	Approved	

Conditioning: Method A

Substrate: Glazing: Glass

IDENTIFICATION:	CH0231T
EDITION:	MAY 2023
VERSION:	1

INGLÊS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH231T

9. Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nuno Miranda
Diretor da QualidadeRaquel Elias
Gestora de Produto

Aveiro (Portugal), 01.06.2023