

# SEALANT REMOVER CHEMICLEAN

## CHEMICLEAN SEALANT REMOVER



## PRODUCT DESCRIPTION

Sealant Remover CHEMICLEAN is a quick, ready-to-use, solvent-based spray, for removing silicone and MS polymers from most substrates, as well as adhesives, tapes and glue residues.

## CHARACTERISTICS

- ✓ Professional quality
- ✓ Slow evaporation
- ✓ Nonaggressive towards most plastics and lacquers.
- ✓ Direct spraying

## TECHNICAL SPECIFICATIONS

Properties	Value
Base	Mixture of hydrocarbons and aliphatic and aromatic alcohols
Color	Clear and colorless
Odor	Typical solvent
Relative density at 20°C	0.79 g/cm <sup>3</sup>
Pressure at 20°C	5,5 bar
Volume	400 ml

Results tested in the laboratory.

## APPLICATIONS

Suitable for removing silicone and MS polymers on most substrates, as well as stickers, tapes and glue residues

## METHOD OF APPLICATION

### PREPARATION

- Before using, shake the can vigorously, which must be at room temperature. The optimum temperature for use is between 10°C and 30°C.

### APPLICATION

- Spray the product on the surface/object to be cleaned.
- Leave to act for 10 to 15 minutes.
- If necessary, wipe with a clean cloth.
- Let it evaporate/dry

## **RESTRICTIONS OF USE**

Due to the wide variety of possible substrates, a prior compatibility test is recommended.

## **SAFETY INFORMATION**

Extremely flammable aerosol. Container under pressure: risk of explosion under the action of heat. Very toxic to aquatic organisms with lasting effects. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of the reach of children.

For more information and advice on safe handling, storage and disposal of chemical products, the user should consult the most recent version of the product's Safety Data Sheet which contains physical, ecological, toxicological and other data related to security.


## **STORAGE CONDITIONS**

Store in a cool, dry and well-ventilated environment, between +10°C and + 35°C, away from sources of heat and humidity.

Validity 10 years if stored under recommended conditions, as this may reduce the shelf life.

After the first use, it should be stored in a cool, dry place, away from heat sources.

## **PACKAGING**

SAP	VOLUME		EAN
CHC030111	400ml	12	5604630178211

**Note:** This technical data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is provided in good faith and supported by various laboratory tests. In view of the diversity of factors which may affect the product during use, as well as the various application techniques, the user is responsible for confirming and carrying out his/her own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is effected under the sole responsibility of the user, and CHEMITOOL - LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.