

SPRAY ALU/PVC CLEANER CHEMICLEAN

CHEMICLEAN SPRAY ALU/PVC CLEANER



PRODUCT DESCRIPTION

SPRAY ALU/PVC CLEANER CHEMISOL Cleaning spray with an active foam with a very intensive effect on dirt particles, grease films, grease residues and traces of superficial oxidation.

CHARACTERISTICS

- ✓ Professional quality
- ✓ The product is not aggressive to paintwork.
- ✓ Can be applied to horizontal and vertical surfaces.
- ✓ Does not contain silicon and has anti-static properties.
- ✓ Due to the rapid degradation of the foam, there will be no "foam residue" in the crevices.

TECHNICAL SPECIFICATIONS

Properties	Value
Base	Mixture of nonionic- and anionic surfactants, glycol, additives and water
Color	White, hazy
Odor	Glycol
Density:	0,99
Pressure at 20°C	3 bar
Volume	400 ml

Results tested in the laboratory.

APPLICATIONS

Advised for cleaning aluminum, PVC, chromium, plastic, glass and enamel windows

METHOD OF APPLICATION

PREPARATION

- Before using, shake the can vigorously, which must be at room temperature. The optimum temperature for use is between 15°C and 25°C.

APPLICATION

- Keep the spraying distance 20-30 cm from the spray area to be treated.
- Wait a few minutes and wipe with a dry cloth.
- Repeat the treatment when necessary.

RESTRICTIONS OF USE

Safe for use on most surfaces and materials. However, surfaces should always be tested in a hidden area first.

SAFETY INFORMATION

Pressurised container: May burst if heated. Extremely flammable aerosol. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

For more information and advice on safe handling, storage and disposal of chemical products, the user should consult the most recent version of the product's Safety Data Sheet which contains physical, ecological, toxicological and other data related to security.


STORAGE CONDITIONS

Store in a cool, dry and well-ventilated environment, between +10°C and +35°C, away from sources of heat and humidity.

Validity 10 years if stored under recommended conditions, as this may reduce the shelf life.

After the first use, it should be stored in a cool, dry place, away from heat sources.

PACKAGING

SAP	VOLUME		EAN
CHC030112	400ml	12	5604630178228

Note: This technical data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is provided in good faith and supported by various laboratory tests. In view of the diversity of factors which may affect the product during use, as well as the various application techniques, the user is responsible for confirming and carrying out his/her own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is effected under the sole responsibility of the user, and CHEMITOOL- LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.