

ADHESIVE SPRAY CHEMIGLU

CHEMICLEAN ADHESIVE SPRAY



PRODUCT DESCRIPTION

ADHESIVE SPRAY CHEMIGLU spray adhesive that bonds a wide variety of materials with high gluing power.

CHARACTERISTICS

- ✓ Professional quality
- ✓ Strong adhesion.
- ✓ Quick drying
- ✓ Moisture resistant.
- ✓ Low viscosity spray glue.
- ✓ Easy to use

TECHNICAL SPECIFICATIONS

| Properties | Value |
|------------------------|---|
| Base | Adhesive based on styrene-butadiene rubber, resins and hydrocarbon solvents |
| Color | White liquid |
| Odor | Typical solvent |
| Temperature resistance | 80°C |
| Density: | 0,7 g/ml |
| Pressure at 20°C | 4 bar |
| Volume | 400 ml |
| Performance | 1,1m ² |

Results tested in the laboratory.

APPLICATIONS

It can be used to glue wood, stone, rubber, canvas fabrics, cardboard, metal, paper, cork, foam, etc.

METHOD OF APPLICATION

PREPARATION

- Before using, shake the can vigorously, which must be at room temperature. The optimum temperature for use is between 10°C and 30°C.
- Surfaces must be clean, dry and free of grease.

APPLICATION

- Spray the product on the surface/object to be glued.
- Gather the pieces to be joined and press.
- Turn the aerosol upside down after use and spray until only gas comes out.
- Remove stains immediately before drying with white spirit or acetone cleaner.

RESTRICTIONS OF USE

Safe for use on most surfaces and materials. However, surfaces should always be tested in a hidden area first.

SAFETY INFORMATION

Extremely flammable aerosol. Container under pressure: risk of explosion under the action of heat. Very toxic to aquatic organisms with long-lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Keep out of the reach of children.

For more information and advice on safe handling, storage and disposal of chemical products, the user should consult the most recent version of the product's Safety Data Sheet which contains physical, ecological, toxicological and other data related to security.

STORAGE CONDITIONS

Store in a cool, dry and well-ventilated environment, between +10°C and + 35°C, away from sources of heat and humidity.

Validity 10 years if stored under recommended conditions, as this may reduce the shelf life.

After the first use, it should be stored in a cool, dry place, away from heat sources.

PACKAGING

| SAP | VOLUME |  | EAN |
|-----------|--------|---|---------------|
| CHC080107 | 400ml | 12 | 5604630196307 |

Note: This technical data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is provided in good faith and supported by various laboratory tests. In view of the diversity of factors which may affect the product during use, as well as the various application techniques, the user is responsible for confirming and carrying out his/her own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is effected under the sole responsibility of the user, and CHEMITOOL- LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.