

MEASURING TAPE FLEX PLUS

CHEMITOOL FLEX PLUS measuring tape with ABS case, drop- and impact-resistant rubber coating, comfortable hand feel.

Compact case, modern design.

Automatic stop button, more convenient to use.

High-performance spring makes the blade retract slowly and safely.

With strong blade, corrosion resistance, moisture resistant.

Blade thickness 0.14mm, nylon coating, 40% thicker than a normal blade.

Blade with high visibility even in dark places.

Double-printed blade, more comfortable and precise.

Double magnetic hook, ideal for vertical measurements.

With belt clip.

- ✓ **Automatic stop button**
- ✓ **High-performance spring with slow retraction**
- ✓ **Corrosion-resistant nylon-coated blade**
- ✓ **Blade thickness 0.14mm**
- ✓ **Double printing on the blade**
- ✓ **Double magnetic hook**
- ✓ **Belt clip**

AREAS OF APPLICATION

- ✓ **Industry**
- ✓ **Construction**

TECHNICAL SPECIFICATIONS

SAP	Length	Width	Thickness	Coating
CHT201515001603	3 mt	16 mm	0,14 mm	Nylon
CHT201515001605	5 mt	25 mm	0,14 mm	Nylon
CHT201515001608	8 mt	25 mm	0,14 mm	Nylon



REFERENCES

SAP	Description	EAN
CHT201515001603	NYLON COATED MEASURING TAPE 3MT - 16MM	5604630167871
CHT201515001605	NYLON COATED MEASURING TAPE 5MT - 25MM	5604630167888
CHT201515001608	NYLON COATED MEASURING TAPE 8MT - 25MM	5604630167895

Nota: Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.