

TROLLEY WITHOUT TRACTION

CHEMITOOL traction-free manual trolley with forged steel wheels mounted on ball bearings. It can be adjusted to a wide variety of beam widths and profiles using the spacer washers.


Widely used in factories, docks, warehouses, construction sites, such as the installation of equipment, suspended goods, especially for the operation of the situation of no power supply.



APPLICATION FIELDS

- ✓ Industry and Construction

TECHNICAL SPECIFICATIONS



SAP	CHT402030500000	CHT402031000000	CHT402032000000	CHT402033000000	CHT402035000000	CHT4020310000000	
Capacity (T)	0,5	1	2	3	5	10	
Beam width (mm)	68-126	80-146	80-168	88-168	100-170	122-203	
Dimensions	A	208	242	280	300	316	343
	B	196	236	273	320	366	389
	C	190	211	236	295	334	460
	H	108	115	130	164	177	237
	F	3	3	3	3	3	3

REFERENCES

SAP	Descrição	EAN
CHT402030500000	MANUAL GEAR TROLLEY WITHOUT TRACTION 0,5T	5604630153041
CHT402031000000	MANUAL GEAR TROLLEY WITHOUT TRACTION 1T	5604630153058
CHT402032000000	MANUAL GEAR TROLLEY WITHOUT TRACTION 2T	5604630153065
CHT402033000000	MANUAL GEAR TROLLEY WITHOUT TRACTION 3T	5604630153072
CHT402035000000	MANUAL GEAR TROLLEY WITHOUT TRACTION 5T	5604630153089
CHT4020310000000	MANUAL GEAR TROLLEY WITHOUT TRACTION 10T	5604630153096

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.