







The CH-25 **CHEMITOOL** Battery Charger is a compact, lightweight and portable device. It has a modern design accompanied by high performance. Easy to use and maintain. Equipped with a selector switch for slow and fast charging.

- √ Single-phase power supply
- ✓ For 12V and 24V batteries
- ✓ Ampermeter



## AREAS OF APPLICATION

- ✓ Car garages
- ✓ Construction sites

## **TECHNICAL SPECIFICATIONS**

Characteristics	CHU020102101250
INPUT VOLTAGE	230 V
SETTING POSITIONS	2
LOAD VOLTAGES	12 / 24 V
MAXIMUM REFERENCE CAPACITY	200 ah
MINIMUM REFERENCE CAPACITY	25 ah
FUSE	3 A





## **REFERENCES**

SAP	Description	EAN
CHU020102101250	BOOSTER BATTERY CHARGER 25Ah	5604630167956

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.