

BOOSTER BATTERY CHARGER

CHEMITOOL portable single-phase booster battery charger for light and heavy vehicles.

With 230V input voltage and 12/24V charging voltage.

Protected against overcharging and reverse polarity. Equipped with ammeter and various plugs available.

Can be used in adverse conditions: IP23C.

- ✓ **Single-phase power supply**
- ✓ **For 12V and 24V batteries**
- ✓ **Ampermeter**



AREAS OF APPLICATION

- ✓ **Car garages**
- ✓ **Construction sites**

TECHNICAL SPECIFICATIONS

Characteristics	CHU020103101400	CHU020103101600
INPUT VOLTAGE	230 V	230 V
NOMINAL WORKING CAPACITY LOAD	1 KW	2 KW
NOMINAL WORKING CAPACITY START	8 KW	12 KW
MAXIMUM STARTING CURRENT	240 A	540 A
SETTING POSITIONS	4	6
LOAD VOLTAGES	12 / 24 V	12 / 24 V
LOAD CURRENT	40 A	60 A
MAXIMUM REFERENCE CAPACITY	700ah	1000 ah
MINIMUM REFERENCE CAPACITY	40ah	60 ah
FUSE	16 A	20 A

REFERENCES

SAP	Description	EAN
CHU020103101400	BOOSTER BATTERY CHARGER 400A	5604630167970
CHU020103101600	BOOSTER BATTERY CHARGER 600A	5604630167987

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.