

BOOSTER BATTERY CHARGER

Portable single-phase battery charger CD-40R **CHEMITOOL** for lead-acid batteries and 12/24V voltage. Protected against overload and reverse polarity, equipped with ammeter. Can be used in adverse conditions: IP23C. The high power available makes it possible to meet all application requirements.



- ✓ Single-phase power supply
- ✓ For 12V and 24V batteries
- ✓ Ampermeter

AREAS OF APPLICATION

- ✓ Car garages
- ✓ Construction sites

TECHNICAL SPECIFICATIONS

Characteristics	CHU020102101400
INPUT VOLTAGE	230 V
NOMINAL WORKING CAPACITY LOAD	0,8 KW
NOMINAL WORKING CAPACITY START	2,5 KW
MAXIMUM STARTING CURRENT	140 A
SETTING POSITIONS	2
LOAD VOLTAGES	12 / 24 V
LOAD CURRENT	25 A
MAXIMUM REFERENCE CAPACITY	500 ah
MINIMUM REFERENCE CAPACITY	20 ah
FUSE	13 A

REFERENCES

SAP	Description	EAN
CHU020102101400	BOOSTER BATTERY CHARGER 25 A	5604630167963

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.