





The PRONYLON CHEMITOOL nylon roller is composed of non-woven material with a thick structure, developed through a special combination of polyester fibres with silicon carbide abrasive grains, and is indicated for operations that require roughing and finishing in the same operation.

- Cold grinding and low thermal load
- ✓ Large working area
- ✓ Don't soggy
- Highly resistant
- ✓ Long tool life

The **CHEMITOOL** nylon drum is suitable for stripping and cleaning work on large surfaces, allowing to increase the speed of work, in which the focus is on uniformity in the cleaning of the piece.

Due to its rigidity, this type of product is not suitable for work in which sharp contours have to be made, but it is possible to carry out operations on surfaces with slight bends.

Suitable for weld cleaning, roughness removal and surface finish.

For best performance, we recommend using it at a speed of 15-30 m/s.

This ensures the optimal compromise between the material removal rate, surface quality, thermal load on the workpiece and tool wear.

Abrasive

Polyester Fibers + Silicon Carbide

Suitable for Steel, stainless steel (stainless steel), non-ferrous metals, plastic

Compatible Machine

Polishing machine



SAP	Grain	Length (mm)	Width (mm)	Shaft Diameter (mm)	Abrasive	RPM	Quantity	EAN
CHA1104100100H	Hard	100	100	19	Polyester Fibers + Silicon Carbide		1	5604630126977

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.



