

# SISAL FLAP WHEEL DRUM PROSISAL

The **PROSISAL CHEMITOOL** sisal flap wheel drum is composed of knotted sisal rope, being indicated for polished or brushed surface finishing operations.



- ✓ **Cold grinding and low thermal load**
- ✓ **Interwoven rope wire**
- ✓ **Large working area**
- ✓ **Highly resistant**
- ✓ **Long tool life**

The **CHEMITOOL** sisal flap wheel drum is suitable for polishing large surfaces, allowing to increase the speed of work, in which the focus is on uniformity in the cleaning of the workpiece.

It can also be used to give a brushed finish, when used in a few passes.

Due to its structure, this type of product allows it to adapt to contours, bearing in mind that the product has a loose structure (rope threads) and can break in contact with sharp edges/angles.

Suitable for pre-polishing work, where it is necessary to remove light scratches on the workpiece.


For best performance, we recommend using it at a speed of 15-30 m/s.

This ensures the optimal compromise between the material removal rate, surface quality, thermal load on the workpiece and tool wear.

**Abrasive**  
Rope Wire (Sisal)

**Suitable for**  
Stainless steel (stainless steel), non-ferrous metals, plastic

**Compatible Machine**  
Polishing machine



SAP	Length (mm)	Width (mm)	Shaft Diameter (mm)	Abrasive	RPM	Quantity	EAN
CHA1202100001	100	100	19	Interwoven rope wire	2500	1	5604630018487

**Note:** The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.