

4-SIDED ABRASIVE BLOCK PROSPONGE 4S

The rectangular **PROSPONGE 4S CHEMITOOL** four-sided abrasive blocks have been specially developed to provide outstanding workability due to their abrasion resistance and special aluminium oxide composition.



- ✓ **Excellent quality/value ratio**
- ✓ **High density**
- ✓ **Easy to use**
- ✓ **Size 98 x 69mm**
- ✓ **26mm thick**
- ✓ **Uniform finish**

The high-density sponge abrasive pad can be used on a wide variety of substrates, such as wood, paints, varnishes and wood coatings. It is best suited to sanding edges and corners.

This type of abrasive block allows it to be used for more aggressive sanding, as well as for preparation/stage sanding.

High-strength binder resin, minimising abrasive grain drop.

Packaged in a two pieces blister pack with display holes.

Abrasive

Aluminium oxide

Suitable for

Wood, varnishes, paints, wood composites and coatings



SAP	Grain	Length (mm)	Width (mm)	Thickness (mm)	Backing	Abrasive	Quantity	EAN
CHA2801098069060	60	98	69	26	High Density Foam	Aluminium Oxide	2	5604630126571
CHA2801098069080	80	98	69	26	High Density Foam	Aluminium Oxide	2	5604630126588
CHA2801098069100	100	98	69	26	High Density Foam	Aluminium Oxide	2	5604630126595
CHA2801098069120	120	98	69	26	High Density Foam	Aluminium Oxide	2	5604630126601
CHA2801098069180	180	98	69	26	High Density Foam	Aluminium Oxide	2	5604630201230
CHA2801098069220	220	98	69	26	High Density Foam	Aluminium Oxide	2	5604630204200

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.