

IDENTIFICATION:	CH0402X
EDITION:	OUT 2024
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH0402X_2024_10

1. Unique identification code of the product-type:

SEAL&BOND PU 40 CHEMIPOL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural use in joints in buildings for exterior and in accordance with the European standard EN 15651-1 (F EXT-INT CC)**Sealant for indoor and outdoor pedestrian walkways (suitable for use in cold climates) in accordance with the European standard EN 15651-4 (PW EXT INT CC)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

CHEMITOOL®
Avenida Europa, 373
3800-533 Cacia – Portugal

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified Body Nº. 1292, carried out the type tests and issued the test report and Notified Body (for fire reaction test) Nº. 370.

IDENTIFICATION:	CH0402X
EDITION:	OUT 2024
VERSION:	1

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH0402X_2024_10

8. Declared performance:

Essential Characteristic	Declared Performance	Harmonized Standard
Reaction to Fire	Classe E	-
Loss of Volume	≤ 10%	EN 15651-1-4
Resistance to flow	≤ 3 mm	
Tensile Properties after immersion in water	NF	
Tensile Properties	>0,4	
Tensile properties for non structural sealants used in cold climates	>0,6	
Tensile Properties at maintained extension	NF	EN 15651-1-4
Tensile Properties at maintained extension-Cold climate	NF	EN 15651-4
Adhesion/Cohesion at variable temperatures	NF	EN 15651-1-4
Tensile Properties after immersion in salt water	NF	EN 15651-4
Tear resistance	NF	EN 15651-4
Durability	Aprovado	EN 15651-1-4

Class: 25 HM
Substrate: Mortar/Glass (Facade Elements)
Substrate: Mortar (Pedestrian Walkways)
NF: No faults


9. Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Nuno Miranda
Diretor da Qualidade



Raquel Elias
Gestora de Produto

Aveiro (Portugal), 01.10.2024