



EN 388:2016



4.2.4.4.X



AMERICAN SPLIT LEATHER GLOVE REINFORCED

American type glove for general use made of split leather and canvas on the cuff with interior cotton coating. Reinforced on the thumb, index finger and palm for extra resistance to abrasion and higher protection. Recommended for construction, metallurgical industry, wood industry, sheet metal handling, naval steel industry, logistics, transport and materials handling, agriculture and gardening.

- ✓ **Split bovine leather**
- ✓ **Cotton lining**
- ✓ **Canvas cuff**
- ✓ **Reinforced palm, thumb and index finger**
- ✓ **Elasticated back**
- ✓ **Excellent resistance to abrasion, tearing and perforation**

TECHNICAL SPECIFICATIONS

Material	BOVINE GRAIN LEATHER, CANVAS AND COTTON
Color	Ecru, grey and blue
Size	10
Packaging	1/10/120
Uses	Construction, metallurgical industry, wood industry, sheet metal handling, naval steel industry, logistics, transport and materials handling, agriculture and gardening.

SAP	SIZE	EAN
CHS02140110	10/XL	5604630021234

CARE, MAINTENANCE AND STORAGE

WARNINGS!

The gloves are suitable only for work where the risks for the user's wrists have been evaluated and found to be insignificant. Protection against risks or hazards which are not mentioned in this document is not guaranteed. These performance levels are obtained from tests carried out according to the conditions defined by the applicable standards. Protection against risks or hazards not mentioned in this document is not guaranteed. Actual conditions cannot be simulated; therefore, it is up to the user to decide whether the gloves are suitable for the intended application or not. The manufacturer is not liable for improper use of the product.

Gloves should not be used where there is a risk of entanglement by moving parts of machines or moving parts. These gloves are not suitable for use or exposure to chemical products. Before use, the gloves should be visually inspected for any defects or imperfections. In case of deterioration, the gloves must be replaced (abrasion, cut, tear, ...). No protection against flames is required. These gloves must not be in contact with flames. The performance levels mentioned are valid only for new, unwashed and unregenerated gloves. The performance levels against mechanical risks are only valid for the glove palm.


STORAGE: Keep in its original packaging in normal temperature and humidity conditions and in a clean, covered and ventilated place.

CLEANING: These gloves are not washable. They may be cleaned with a soft, damp cloth.

PPE SUBJECT TO AGING: Product performance is not affected by aging when stored under proper conditions of humidity, temperature, cleanliness, ventilation and light.

EU Declaration of Conformity available at: www.chemitool.com

Applicable standards: EN ISO 21420:2020 "Protective gloves - General requirements and test methods" - Dexterity: 4 | EN 388:2016+A1:2018 "Mechanical risks"

MECHANICAL HAZARDS: EN 388:2016 + A1:2018		LEVELS OF PERFORMANCE	
 EN 388:2016 4.2.4.4.X	ABRASION RESISTANCE	4	(from 1 to 4)
	BLADE CUT RESISTANCE	2	(from 1 to 5)
	TEAR RESISTANCE	4	(from 1 to 4)
	PUNCTURE RESISTANCE	4	(from 1 to 4)
	CUT RESISTANCE method (EN ISO 13997)	X	(from A to F)
	IMPACT PROTECTION	X	
"X" indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material. "0" indicates that the glove falls below the minimum performance level for the individual hazard.			

These gloves are a personal protective equipment belonging to category II. They comply with the requirements of the PPE Regulation 2016/425: safety, comfort, soundness, EN ISO 21420:2020 "Protective gloves - General requirements and test methods" and EN 388:2016+A1:2018 "Mechanical hazards".

PPE subject to an EU type-examination carried out by :
Bureau Veritas (2004)
Services Germany GmbH
Wilhelm-hennemann-Strasse 8
19061 Schwerin